



Desktop configuration
easily converts to
wall mount solution



Built to Compete...

...our New Fan-Free KS6215 POS Bundle fits today's economy!

Introducing the KS6215 Bundle – our newest fan-free, high performance POS terminal that is available at a very attractive price point you will love. Not a limited offer, the KS6215 is a standard product featuring our patented aluminum chassis for maximum heat dissipation, a 1.5GHz CPU, bundled with a 2-track MSR and Microsoft® Windows® Embedded for Point-Of-Service. Available in a desktop configuration which easily converts to a wall mount solution. The KS6215 is ideally suited to end-users looking for value and an attractive price with no compromise on quality. Call today and find out how the new KS6215 can boost your sales and help GROW your bottom line.

For more information call (888) 968-1668 today!

Authorized Posiflex Distributors:



KS6215 Value Bundle Features

- FAN-FREE! Runs cool (no fans, heat pipes or liquids)
- 1.5GHz VIA C7 Processor w/128KB L-2 cache
- 80GB SATA HDD
- 512MB DDR2 RAM
- Microsoft® WEPOS® Operating System ("plug and play" functionality)
- SD402 2-track Magnetic Stripe Reader
- Built for harsh environments
- Durable 15" touch screen
- Rapid Exchange & Onsite Service (Optional)
- Private label front bezel logo*

www.posiflexusa.com

* Minimum order requirements may apply

© 2008 Posiflex Business Machines, Inc. Posiflex and KS are trademarks of Posiflex Business Machines, Inc. All other brand and company names are the property of their respective owners.



Processor	VIA C7 1.5GHz
Memory	Standard 512MB, DDR2 SDRAM SO-DIMM x 1
VGA Memory	16MB - 64MB (shared)
Power Supply	12V DC power adaptor, 80W
Housing	Aluminum die casting
Speaker	Built-in
OS Support	Microsoft® WEPOS
Safety Certifications	FCC-A, CE-A, RoHS WEEE
LCD	15" LCD, 200nits, 1024 x 768 XGA
Touch Sensor	Resistive
Touch Controller	USB interface mouse emulation
Tilt Adjustment	From 17.5° to 76.5°
Storage Device	80GB SATA HDD
Mounting Option	Desktop or wallmount (wallmount bracket sold separately)
Audio Port	2 Watt audio output built-in
LAN Port	1 x 10/100 Base T Ethernet
Parallel Port	1 x SPP / EPP / ECP
Serial Port	2 x DB9, each with +5V / +12V power supply capability
UPS Port	N/A
USB Port	4 x, USB 2.0 + 1 proprietary port for SD-402
PS/2 Mouse Port	N/A
KB Port	N/A
CR Port	1 x, for single cash drawer, 12V DC
Operation Condition	0°C~+40°C (32°F~+104°F), 20%RH~80%RH, non-condensing max. wet bulb 26°C (78.8°F)
Storage Condition	-20°C~+60°C (-4°F~+140°F), 10%RH~80%RH, non-condensing max. wet bulb 28.9°C (84.0°F)
2nd LCD Display	LM6101B
Customer Pole Display	PD2501: 11mm, 2x20 VFD display, 5x7 dot matrix, RS232 interface PD2602: 9mm, 2x20 VFD display, 5x7 dot matrix, RS232 or USB interface PD305: 9mm, 2x20 LCD display, 5x7 dot matrix, RS232 or USB interface
SD-402 Magnetic Stripe Reader	Optional 2-track or 3-track MSR with/without Finger Print Sensor

